CLEVE™

Porcelain Stone®

CROSSVILLE®

Available Colors

CLV01 Ivory Ridge

CLV02 Strata Beige

CLV03 Shadow Glen

CLV04 Iron Hollow

Features and Benefits

- Cleve™ channels the authentic character of quartzite—stone split along its natural planes—revealing crystalline sparkle, tonal depth, and layered veining.
- Rectified field tile sizes: 12”x 24”, 24”x 24” and 24”x 48”
- 2”x4” Stacked and 8-pc Mod-Hex Mosaic
- Complete your installations with 4”x 24” bullnose or 6”x 12” cove base
- The collection features Crossville’s proprietary FeatherSoft™ finish, a smooth matte surface
- Made in the USA with global and domestic components

CLEVE™

Porcelain Stone®

CROSSVILLE®

Available Mosaics

CLV01.10204FMOS
Ivory Ridge
2 x 4 Stacked Mosaic

CLV02.10204FMOS
Strata Beige
2 x 4 Stacked Mosaic

CLV03.10204FMOS
Shadow Glen
2 x 4 Stacked Mosaic

CLV04.10204FMOS
Iron Hollow
2 x 4 Stacked Mosaic

CLV01.1MHEXFMOS
Ivory Ridge
8-pc Mod-Hex Mosaic

CLV02.1MHEXFMOS
Strata Beige
8-pc Mod-Hex Mosaic

CLV03.1MHEXFMOS
Shadow Glen
8-pc Mod-Hex Mosaic

CLV04.1MHEXFMOS
Iron Hollow
8-pc Mod-Hex Mosaic

Crossville • 349 Sweeney Drive, Crossville, Tennessee 38557 • Phone: 931.484.2110 • Fax: 931.456.2956 • E-Mail: Crossc@CrossvilleInc.com • Crossville.com

CLEVE™

Porcelain Stone®

CROSSVILLE®

Sizes





2 x 4 Stacked Mosaic
Mounted on a 296.9 x 296.9 sheet (coverage area 0.98sf)

8-pc Mod-Hex Mosaic
Mounted on a 267 x 371 sheet (coverage area 0.81sf)

4 x 24 Single Bullnose



6 x 12 Cove Base

Get Planked!

Our Porcelain Stone® products are available in popular plank shapes with no minimum order and quick fulfilment.

See website for more details and sizes.

GET PLANKED®

Sizes & Finishes

Field Tile - Rectified

Available in all colors

Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
12 x 24	297 x 597	9.5	3	FST
24 x 24	597 x 597	9.5	3	FST
24 x 48	597 x 1197	10.5	3	FST

Note: Field tile is rectified with a 3mm grout joint

Mosaics

Available in all colors

Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
2 x 4 Stacked Mosaic	296.9 x 296.9*	9.5	2.5	FST
8-pc Mod-Hex Mosaic	267 x 371†	9.5	2.2	FST

* Mounted on 12 x 12 sheet (coverage area 0.98sf) † Mounted on 10 x 15 sheet (coverage area 0.81sf)

Coordinating Trim

Available in all colors

Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
4 x 24 Single Bullnose	97 x 597	9.5	3	FST
6 x 12 Cove Base	150 x 297	9.5	3	UPS

Product Performance

Water Absorbtion	<0.5%	ASTM (C373)
Breaking Strength	≥ 450 lbf	ASTM (C648)
Bond Strength	> 200 psi	ASTM (C482)
Facial dimension	± 0.10%	ASTM (C499)
Range of Thickness (in)	0.025	ASTM (C499
Warpage - diagonal	± 0.20%	ASTM (C485)
Wedging	± 0.25%	ASTM (C502)
Frost (Freeze/Thaw) Resistance	Resistant	ASTM (C1026)
Chemical Resistance	Unaffected	ASTM (C650)
Stain Resistance	Class A	ASTM (C1378)
Scratch Hardness	7	(Mohs)
Deep Abrasion	na	ASTM (C1243)
Crazing Resistance	Resistant	ASTM (C424)
Thermal Shock Resistance	Resistant	ASTM (C484)
Visible Abrasion Resistance	na	ASTM (C1027)

Wet Dynamic Coefficient of Friction Range

FST	0.50 - 0.60	ANSI (A326.3)

Shade & Texture Index

Cleve has a shade variation of V4.



V1 Uniform appearance
V2 Slight Variation
V3 Moderate Variation
V4 Substantial Variation

This porcelain tile product is produced with a V4 variation. While the colors and/or textures present on a single piece of tile will be indicative of the colors and/or textures to be expected on the other tiles, the amount of colors and/or texture on each piece may vary significantly. It is recommended that the range be viewed before selection.

Crossville • 349 Sweeney Drive, Crossville, Tennessee 38557 • Phone: 931.484.2110 • Fax: 931.456.2956 • E-Mail: Crossc@CrossvilleInc.com • Crossville.com

CLEVE™

Crossville®
349 Sweeney Drive
Crossville, TN 38555

Phone 931.484.2110
Fax 931.456.2956
E-Mail Crossc@CrossvilleInc.com
Web Crossville.com

Application Areas

Please see Application Area chart at Crossville.com/learn/specification-library

Recommended Use

Cleve is recommended for interior floors, interior walls, countertops, exterior walls, pool waterlines and full linings† in both residential and commercial applications. Cleve is not recommended for exterior horizontal surfaces or exterior paving. See Crossville.com for detailed installation instructions

† Excludes mesh mounted mosaics.

Wet area use for Cleve Mosaics

Crossville® produces the Cleve 2 x 4 mosaic and 8-pc Mod-Hex Mosaic with the FeatherSoft™ (FST) finish. The ANSI A326.3 wet Dynamic COF of Cleve is ≥0.50. Their small sizes ensure frequent grout joints which provides traction and drainage. Crossville cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water and poor surface cleaning. This information is provided so that customers may make a realistic and informed decision when comparing Cleve to other tile products in wet area environments, such as residential/commercial bathrooms, showers, and interior pool decks.

Care and Maintenance

Regular cleaning is the best way to keep Cleve tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More information regarding the care and maintenance of Crossville® products is available at Crossville.com.

Our Warranty

Crossville guarantees that it's products will meet or exceed the performance specifications outlined in ANSI A137.1 and in the performance data section of the Crossville general product catalog. For complete details check our website at Crossville.com

Information listed here is subject to change. Please refer to Crossville.com for the latest, most accurate information.

Crossville® Sample Express

Visit the website to learn more:

Crossville.com/Products/Cleve

Loose Tile Samples
Sizes may vary depending on product series
Max. of 4 large field tile per order

Standard Shipping
FedEx Ground

Crossville.com

You'll find comprehensive information about Crossville's entire portfolio of products. You can also learn about the latest styles and trends from industry experts, download detailed care and maintenance instructions for our various products, or browse electronic versions of Crossville's product brochures. So whether you need information about Crossville products or tile in general,please visit us at Crossville.com.

Trade Organizations

Environmentally Aware

FS-CLV-26

©2026 AHF, LLC. All trademarks are owned by AHF, LLC or it's subsidiaries or affiliates. | Printed in USA
Note: Due to printing limitations, colors pictured cannot be guaranteed to match actual material.